

## Two Stage Bare Units

### Standard Features Include:

- Flywheel
- Dry Type Inlet Filters
- ASME Intercooler and Discharge Safety Valves

## Specifications

Model	No. Cyls.	Bore LP/HP Inches	Stroke Inches	HP Range	Speed Range RPM	Normal Press. Range PSI	Normal Displ. Range CFM
321TV	2	3½ & 1¾	3	1-1½-2	350/823	50-200*	4.3/12.8
332TV	2	4¾ & 2½	4	3-5	345/668	50-200*	14.1/31.7
335TV	2	4¾ & 2½	3	3-5	418/810	60-200*	12.8/27.4
352TV	2	5½ & 3	5	7½-10	520/657	60-200*	36.0/45.0
452TV	4	4¾ & 2½	3	7½-10	590/846	60-200*	36.0/56.5
462TV	4	5½ & 3	5	15-20-25	465/775	60-200*	64.0/106.5

NOTE: For constant speed control, add suffix letter "X" to Model No. For example: 332TVX.

NOTE: Special applications to 250 PSIG suitable under certain conditions.

## Dimensions:

MODEL	A	B	C	D	E	F	G
321TV	17 <sup>5</sup> / <sub>16</sub>	4 <sup>3</sup> / <sub>8</sub>	9	6 <sup>1</sup> / <sub>4</sub>	2 <sup>1</sup> / <sub>2</sub>	2 <sup>1</sup> / <sub>2</sub>	15
332TV	21 <sup>3</sup> / <sub>32</sub>	5 <sup>1</sup> / <sub>2</sub>	10 <sup>5</sup> / <sub>8</sub>	6 <sup>1</sup> / <sub>4</sub>	3 <sup>1</sup> / <sub>2</sub>	3 <sup>3</sup> / <sub>32</sub>	23
335TV	17 <sup>7</sup> / <sub>8</sub>	4 <sup>3</sup> / <sub>8</sub>	9	6 <sup>1</sup> / <sub>4</sub>	2 <sup>1</sup> / <sub>2</sub>	2 <sup>1</sup> / <sub>2</sub>	15
352TV	27 <sup>1</sup> / <sub>2</sub>	7	14 <sup>1</sup> / <sub>2</sub>	10	5 <sup>5</sup> / <sub>8</sub>	4 <sup>7</sup> / <sub>8</sub>	30 <sup>1</sup> / <sub>2</sub>
452TV	18 <sup>5</sup> / <sub>8</sub>	5 <sup>3</sup> / <sub>4</sub>	10 <sup>5</sup> / <sub>8</sub>	6 <sup>1</sup> / <sub>4</sub>	3 <sup>1</sup> / <sub>4</sub>	3 <sup>3</sup> / <sub>32</sub>	17 <sup>3</sup> / <sub>8</sub>
462TV	31	7 <sup>15</sup> / <sub>16</sub>	16	10	4 <sup>11</sup> / <sub>16</sub>	4 <sup>13</sup> / <sub>16</sub>	25 <sup>1</sup> / <sub>2</sub>

  

MODEL	H	J	K	L	M	P	Wt
321TV	13 <sup>3</sup> / <sub>4</sub>	½	1 <sup>1</sup> / <sub>32</sub>	1	19½	¾	120
332TV	18	¾	1 <sup>7</sup> / <sub>32</sub>	1.374	26¼	1	200
335TV	13¾	¾	1 <sup>1</sup> / <sub>32</sub>	1	17¾	1	100
352TV	25¼	¾	2 <sup>5</sup> / <sub>32</sub>	2.185	35½	1½	520
452TV	18	1	1 <sup>11</sup> / <sub>32</sub>	1 <sup>3</sup> / <sub>8</sub>	20 <sup>1</sup> / <sub>8</sub>	1½	275
462TV	25¼	¾	2 <sup>5</sup> / <sub>32</sub>	2.185	34	1½	790

